

Union Flat BW/F

| CF8M (1.4408, V4A) | ISO7-1 (Rp)

Article No.	Standard		Dimension (mm)			
	Size	DN	A	B	C	BW
21350102	1/4	8	35.3	29	18	13.7
21350103	3/8	10	37.2	34	21.9	17.2
21350104	1/2	15	39	37.5	25	21.3
21350105	3/4	20	41.5	44.5	31	26.9
21350106	1	25	48.5	53.5	38.2	33.7
21350107	1-1/4	32	49.8	64	47	42.4
21350108	1-1/2	40	54	71.5	53.5	48.3
21350109	2	50	60	85.5	66	60.3
21350110	2-1/2	65	80	108.5	85	76.1
21350111	3	80	91	123.5	98.2	88.9

- PN20 /300lbs cast fittings, CF8M (1.4408, V4A) cast version of 316 (1.4401)
- Thread acc. to ISO 7-1, DIN EN 10226-1 (old DIN 2999 & BS21); parallel female thread Rp (BSPT).
- With PTFE gasket.
- Pressure ratings:

Temperature C°	Non-shock max. working pressure bar
-20 to 40	20
100	16.5
150	10

*Temperatures indicated are those of internal fluid
Piping loads, stresses and moments are not taken into account.

