

Red. Socket G-Thread ISO 228

| CF8M (1.4408, V4A) | ISO228-1 (G)

Article No.	Standard		Dimension (mm)	
	Size		A	B
G21190002	1/4	1/8	18.5	24.9
G21190003	3/8	1/8	22	27.1
G21190004		1/4	22	29
G21190029	1/2	1/8	26	21
G21190005		1/4	26	25
G21190006		3/8	26	28
G21190030	3/4	1/4	32	24
G21190007		3/8	32	24.5
G21190008		1/2	32	32.5
G21190023	1	3/8	39	27
G21190009		1/2	39	29.5
G21190010		3/4	39	36.4
G21190028	1-1/4	1/2	48	32
G21190011		3/4	48	33
G21190012		1	48	42
G21190024	1-1/2	3/4	54	33
G21190013		1	54	34.5
G21190014		1 1/4	54	44.3
G21190025	2	1	66	38
G21190015		1 1/4	66	40
G21190016		1 1/2	66	47.8

- PN20 /300lbs cast fittings, CF8M (1.4408, V4A) cast version of 316 (1.4401)
- Thread acc. to ISO 228-1 (old DIN 259 & BS2779); parallel female thread G (BSPP).
- Pressure ratings:

Temperature C°	Non-shock max. working pressure bar
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

*Temperatures indicated are those of internal fluid
Piping loads, stresses and moments are not taken into account.

